





Windstorm Mitigation Inspection

Inclusions:

- A. Uniform Mitigation Verification Inspection Form OIR-B1-1802
- B. One complete set of supporting supporting digital color photos
- C. Deficiency Report (if applicable)



121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009

Inspector Initials EL







Uniform Mitigation Verification Inspection Form: Maintain a copy of this form and any documentation provided with the insurance policy.

This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155

					DATE 4/7/2021			
ADDRESS				COUNTY				
121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33	009			BROW	ARD			
PHONE			STORIES	AGENT	_			
239-330-0289 EMAIL	CARRIER /	1970 / POLICY #	14	Amand	UNIT / BU	II DING#		
TID20042@HOTMAIL.COM	oratical.tr	71 02:01 #			1	ERENCE ONLY		
NOTE: Any documentation used in validating the compliance	e or exist	tence of each construction or mitig	ation attrib	ute must accompar	L ny this form	. At least one photograph must		
accompany this form to validate each attribute marked in qu				•	-	. • .		
1.Building Code: Was the structure built in complian	nce with t	the Florida Building Code (FBC 2	001 or late	er)				
OR for homes located in the HVH					BC-94)?			
A. Built Complying With FBC Year Built		Home	es built in 2	002/2003 provide	a permit a	pplication with		
a date after 3/1/2002: Building Permit Application Date	(MM/DD	D/YYYY)						
B. For the HVHZ Only: Built in compliance with the SFB	C-94: Yea	ar Built Application Date (MM/I	DD/YYYY)	For home	s built in 1	994,1995, & 1996		
provide a permit application with a date after 9/1/1994:	-							
 C. Unknown or does not meet the requirements of Answer 	wer "A" oı	r "B"						
2. Roof Covering: Select all roof covering types in	n use. Pr	rovide the permit application date	OR FBC/N	MDC Product App	roval numb	er OR Year of Original		
Installation/Replacement OR in	ndicate th	hat no information was available t	to verify co	mpliance for each	roof cove	ring identified		
2.1 Roof Covering Type: Permit Application	n Date	FBC or MDC Product Approv	val# Yea	ar of Original Inst	allation	No Information Provided for		
				or Replaceme	nt	Compliance		
1 Acabalt/Eibarglass Shingla								
1. Asphalt/Fiberglass Shingle 2. Concrete/Clay Tile								
3. Metal								
4. Built-up 5/20/15		2015-1893-NRPR-0		2015				
5. Membrane								
6. Other								
A. All roof coverings listed above meet the FBC with a FBC or the roof is original and built in 2004 or later.	r Miami-Dao	de Product Approval listing current at ti	me of installa	ation OR have a roofir	g permit app	lication date on or after 3/1/02 OR		
B. All roof coverings have a Miami-Dade Product Approval lis	ting curren	nt at time of installation OR (for the HVH	Z only) a roo	fing permit application	n after 9/1/19	94 and before 3/1/2002 OR the roof		
is original and built in 1997 or later.								
C. One or more roof coverings do not meet the requirements		"A" or "B".						
D. No roof coverings meet the requirements of Answer "A" or	• "В".							
3. Roof Deck Attachment: What is the weakest form of roof deck attachment?								
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field OR Batten decking supporting wood shakes or wood shingles OR Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.								
B. Plywood/OSB roof sheathing with a minimum thickness of								
inches in the fieldOR- Any system of screws, nails, adhesive			ing that is sh	nown to have an equiv	alent or grea	ter resistance 8d nails spaced a		
maximum of 12 inches in the field or has a mean uplift resistant C. Plywood/OSB roof sheathing with a minimum thickness of		·	a maximum (of 24"inches o.c.) by	Rd common n	ails spaced a maximum of 6"		
C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any								
system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.								
D. Deinfersed Consents Book Book	o2 poi.							
E. Other								
F. Unknown or unidentified								
G. No attic access								
_								

Property Address 121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009







What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within

4. Roof to Wall Atta	achment: What is the WEAKEST roof to	wall connection? (Do no	t include attachment of hip/valley jack	s within			
	5 feet of the inside or outside	corner of the roof in dete	rmination of WEAKEST type)				
A. Toe Nails							
7 100 1140	Truss/rafter anchored to top plate of wall using	nails driven at an angle th	rough the truss/rafter and attached to th	e top plate of the wall, or			
	Metal connectors that do not meet the minimal	-	•				
			, ,				
B Clips	Metal connectors that do not wrap over the to	op of the truss/rafter, or					
	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.						
C. Single Wraps	Metal connectors consisting of a single strap	that wraps over the top o	f the truss/rafter and is secured with a m	inimum of 2 nails on the front side and a			
_	minimum of 1 nail on the opposing side.						
D. Double Wraps	D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or						
	Metal connectors consisting of a single strap			., -			
	with a minimum of three nails on each side.		,				
E. Structural - And	chor bolts structurally connected / reinforced concrete	roof.					
F. Other:		G. Unknown or i	unidentified	H. No attic access			
				J			
5. Roof Geometry:	• • • • • • • • • • • • • • • • • • • •		•	wall of the host structure over unenclosed space in			
	the determination of roof perimeter or roof are Hip roof with no other roof shapes greater tha	• ,	,				
A. Hip Roof	The roof with no other roof shapes greater tha	ii 10 % of the total 1001 sy	stem perimeter.				
	Total length of non-hip features:	feet:	Total roof system perimeter:	feet			
B. Flat Roof	Roof on a building with 5 or more units where	at least 90% of the main	roof area has a roof slope of less than	n 2:12.			
	Roof area with slope less than 2:12	sq ft: Total roof	area sq ft				
C. Other Roof	Any roof that does not qualify as either (A) or	(B) above.					
6. Secondary Wate	r Resistance (SWR): (standard underlay	ments or hot-mopped fe	lts do not qualify as an SWR)				
A. SWR (also cal	Illed Sealed Roof Deck) Self-adhering polymer mo	_		-			
☐ B. No SWR	•						
C. Unknown or i	undetermined						
Inspector Initials EL	Property Address 121 GOLDEN ISLES D	R, HALLANDALE BEACI	HFL 33009				

Inspector Initials EL

Property Address







Uniform Mitigation Verification Inspection Form. Maintain a copy of this form and any documentation provided with the insurance policy.

This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155

Opening Protection Level Chart 7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.			Glazed Openings				Non-Glazed Openings	
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	N/A Not Applicable- there are no openings of this type on the structure		X	X	X		X	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)	✓				✓		
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance.							
N	Opening Protection products that appear to be A or B but are not verified							
	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection							
	A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). • Miami-Dade County PA 201, 202, and 203 • For Garage Doors Only: ANSI/DASMA 115 • For Skylights Only: ASTM E 1886 and ASTM E 1996 • Southern Standards Technical Document (SSTD) 12 • Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 • American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996. • A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist							
\cup	A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above							
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): • ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb. • SSTD 12 (Large Missile – 4 lb. to 8 lb.) • For Skylights Only: ASTM E 1886 & ASTM E 1996 (Large Missile 2 to 4.5 lb.)								
	C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).							
	N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected with protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B" with no documentation of compliance (Level N in the table above).							
	X. None or Some Glazed Openings One or more Glazed openings classified and Level X in the table above.							

121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009







		TION INSPECTIONS MUS. 711(2), Florida Statutes, pr					
Qualif	ied Inspector Name:	3 1447	License Type:	208 208 3 20 20 20 3	License or Certificate #		
	HAEL DIGIORGIO		CGC		033997		
Inspection Company: FLEET INSPECTIONS					Phone: (954) 752 9443		
Qualifi	Construction Industry Licensing Bo Building code inspector certified ur General, building or resion Professional engineer licensed und Professional architect licensed und	ction 468.8314, Florida Statutes who heard and completion of a proficiency extender Section 468.607, Florida Statutes. Idential contractor licensed under Section 471.015, Florida Statutes. Idential statutes. Idential Statutes. Idential Statutes. Idential Statutes.	as completed the statutory number am. nder Section 489.111, Flo	orida Statutes.	ane mitigation training approved by the		
l,	MICHAEL DIGIORGIO (print name) I had my employee (Eli Levr	requisite skill, knowledge, and exp am a qualified inspector and I personly)	erience to conduct a mitigation	verification inspe	nt name)contractors and professional engineers		
Qua	lified inspector signature:	W	04/07/2021				
ne Flo Sectio	rida Division of Insurance Frau n 627.711(4)-(7), Florida Statut	ıd and may be subject to admin	istrative action by the appro certifies this form shall be	priate licensing	fication form is subject to investigation by agency or to criminal prosecution. or the misconduct of employees as if the		
		certify that the named Quan and that proof of identific			ee did perform an inspection of the horized Representative.		
Sig	nature:		Date:	<u>04/07/2021</u>			

The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.

An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)

Inspector Initials EL Property Address 121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009







TO VIEW DEFICIENCY PHOTOS PLEASE GO BACK TO THE PREVIOUS PAGE

121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009

PHOTO PAGES

ELEVATION













121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009

UNGLAZED OPENINGS



















121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009

GLAZED OPENINGS





















(954) 752-9443 (888) 505-0828



Uniform Mitigation Verification Inspection Form. Maintain a copy of this form and any documentation provided with the insurance policy.

This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155















GLAZED OPENINGS II































121 GOLDEN ISLES DR, HALLANDALE BEACH FL 33009

ROOF COVERING



